



ARP 573936N 0121728E

AD ELEV 507 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking	Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar
A	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	Stopbar
B	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
C	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
D	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
E	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
F	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
G	23 m	ASPH PCN 70 F/B/X/T	CL	CL	
H	23 m	ASPH PCN 70 F/B/X/T	CL	CL	
J	23 m	ASPH PCN 70 F/B/X/T	CL	CL	
K	23 m	ASPH PCN 70 F/B/X/T	CL	CL	
L	23 m	ASPH PCN 70 F/B/X/T	CL	CL	
Y	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	RGL Stopbar
Z	23 m	ASPH PCN 70 F/B/X/T	CL HLDG	CL	Stopbar

REMARKS:  
Apron TWY surface and bearing strength; ASPH, PCN 70 F/B/X/T

TWY B, C, D, E, F, Y: Centreline on exit TWY:s within ILS critical/sensitive areas and centreline within 150 m from RWY centreline -alternately green and yellow

MAX wingspan 52 m on TWY D.

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
Apron CONC+ASPH		See AD 2 ESGG 2-4	