



ARP 560507N 0131225E

AD ELEV 139 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting
			Centerline Holding	Edge Centerline	
A	8 m	CONC PCN	CL HLDG	EDGE HLDG	RGL Stopbar
B	10 m	CONC+ASPH PCN	CL HLDG	EDGE HLDG	RGL
C	8 m	CONC PCN	CL HLDG		
D	10 m	CONC PCN	CL HLDG		
E	10 m	CONC PCN	CL HLDG		
F	10 m	CONC PCN	CL HLDG		
H	8 m	ASPH PCN	CL		
J	4.8 m	ASPH PCN	CL HLDG		RGL
K	8 m	CONC PCN	CL	EDGE	
Y	8 m	CONC+ASPH PCN	CL HLDG	EDGE	RGL

INS Coordinates for Aircraft Stands		
APRON Surface Bearing strength	NR	COORD
1 CONC PCN		
2 CONC PCN		
3 CONC PCN		
4 CONC PCN		
5 CONC PCN		

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
11R	113.86° GEO 109° MAG	560511.45N 0131052.36E GUND 119 ft	PCN 25 R/B/X/T	THR 123 ft	1986	1986	1986	1986		THR Green	APAPI Left/3.00°	1986/60 m White Caution zone 600 m yellow LIH	Red
29L	293.89° GEO 289° MAG	560445.46N 0131237.35E GUND 119.3 ft	PCN 25 R/B/X/T	THR 136.1 ft TDZ 136 ft	1986	1986	1986	1986	Calvert Cat I 750 m LIL/LIH	THR Green WBAR	PAPI Left/3.00° (57.4 ft)	1986/60 m White Caution zone 600 m yellow LIH	Red
11L	113.04° GEO 108° MAG	560518.61N 0131133.02E GUND 119 ft	PCN 25 R/B/X/T	THR 126 ft	1998	1998	1998	1998					
29R	293.06° GEO 288° MAG	560453.31N 0131319.36E GUND 119 ft	PCN 25 R/B/X/T	THR 139 ft	1998	1998	1998	1998					