


STOCKHOLM/Arlanda
RNP RWY 19L
(LNAV/VNAV, LNAV only)



560
184°
O HEADING 148°
1500,
FORING FOR
OACH.

(MAPt)
RW19L

SDF 5.0
(LNAV only)
1740

VPA 3.0° (5.2%)
184° (190.5°T)

(FAF/FAP)
SA530
2500

(IF)
AGILI
2500

184°

From radar vectors

148°
SA560
184°

OCA(H)
700
920

5 NM
0
5
10

OCA (H)					Final approach	Distance FAF-MAPt 7.4 NM						
Cat of ACFT	A	B	C	D	Dist to RW19L	2	3	4	5	6	7	
LNAV/VNAV	463 (365)	468 (370)	473 (375)	479 (381)	ALT	786	1104	1423	1741	2060	2378	
LNAV	530 (440)				GS	kt	80	100	120	140	160	180
					Rate of descent	ft/min	425	530	635	745	850	955

AIRAC AIP AMDT 3/2025

STOCKHOLM/Arlanda

RNP RWY 19L via AGILI

Path Term	Waypoint Identifier	Fly-over	Course °M(°T)	Dist (NM)	Turn Dir	Rest Alts (ft AMSL)	Speed Limits (kt)	VPA/ RDH (°/ft)	Rec Navaid	Navigation Specification
IF	AGILI	-	-	-	-	+2500	-210	-	-	RNP APCH
TF	SA530	-	184° (190.5°)	3.5	-	@2500	-	-	-	RNP APCH
TF	RW19L	Y	184° (190.5°)	7.4	-	@149	-	-3.00/50	-	RNP APCH
CF	SA560	Y	184° (190.5°)	2.1	-	-	-	-	ARL	RNP APCH
VM	-	-	148°	-	L	@1500	-	-	-	RNP APCH