



ARP 602520N 0153054E

AD ELEV 504 FEET

LEGEND See GEN 2.3

DMN in M, ELEV in FT

TWY NR	WIDTH	Surface Bearing Strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL
A	23 m	ASPH PCN 50 F/B/X/U	CL HLDG	EDGE		RGL
B	10 m	ASPH	CL HLDG			RGL

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
ASPH PCN 50 F/B/X/U			

REMARK : REDL located 4.5 m from RWY edge.

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing Strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
14	132.41° GEO 127° MAG	602544.73N 0152959.51E GUND 95 ft	PCN 50 F/B/X/T	THR 504 ft	2313	2513	2313	2313	SALS 420 m LIL/LIH	THR Green	PAPI Left/3.25° (65.2 ft)	2313/60 m White Caution zone 600 m yellow LIL/LIH	Red
32	312.44° GEO 307° MAG	602454.32N 0153151.09E GUND 94.7 ft	PCN 50 F/B/X/T	THR 493.0 ft TDZ 495.3 ft	2313	2313	2313	2313	Calvert Cat I 900 m LIL/LIH	THR Green	PAPI Left/3.00° (60.7 ft)	2313/60 m White Caution zone 600 m yellow LIL/LIH	Red
12	117.94° GEO 113° MAG	602542.84N 0152923.26E GUND 95 ft		THR 506 ft	720	720	720	720					
30	297.95° GEO 293° MAG	602531.94N 0153004.83E GUND 95 ft		THR 501 ft	720	720	720	720					

