



ARP 592116N 0175632E  
AD ELEV 47 FEET

LEGEND See GEN 2.3  
Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking Centerline Holding	Taxiway lighting Edge Centerline Stopbar	RGL Stopbar
G1	20 m	PCN 9 F/B/X/T	CL HLDG	EDGE STOPBAR	
R	16 m	PCN 40 F/A/X/T	CL	CL	
S	15 m	PCN 120 F/A/X/T	CL	CL	
T	19 m	PCN 100 F/A/X/T	CL	CL	
Y	19 m	PCN 59 F/A/X/T	CL	CL	
Y1	19 m	PCN 60 F/A/X/T	CL HLDG	CL	RGL STOPBAR
Y2	20 m	PCN 38 F/B/X/T	CL ITHP	CL	
Y3	19 m	PCN 64 F/A/X/T	CL HLDG	CL	RGL STOPBAR
Y4	19 m	PCN 55 F/B/X/T	CL HLDG	CL	RGL STOPBAR
Y5	19 m	PCN 38 F/A/X/T	CL HLDG	CL	RGL STOPBAR
YU	24 m	PCN 71 F/A/X/T	CL ITHP	CL	
YW	24 m	PCN 103 F/A/X/T	CL ITHP	CL	

REMARK: Pilot will receive instructions to change to GND frequency from TWR after landing.

APRON Bearing strength	NR	COORD	ELEV
Apron 1 ASPH PCN 82 F/B/X/T	3	592118.27 N 0175641.31 E	18
	4	592119.31 N 0175638.60 E	17
	5	592120.29 N 0175635.90 E	18
	6	592121.09 N 0175633.30 E	18
Apron 2 ASPH PCN 85 F/B/X/T	7	592123.37 N 0175630.63 E	18
	8	592122.78 N 0175632.72 E	18
	9	592121.82 N 0175635.41 E	17
	10	592120.96 N 0175639.17 E	18
Apron 3 ASPH PCN 80 F/B/X/T	11	592123.33 N 0175640.65E	16
	12	592125.10 N 0175639.26 E	15
	13	592126.18 N 0175636.24 E	16
	14	592127.26 N 0175633.22 E	18
Apron 4 ASPH PCN 44 F/B/X/T	15	592128.16 N 0175630.31 E	18
	16	592128.95 N 0175633.26 E	19
	17	592128.02 N 0175635.87 E	18
	18	592126.93 N 0175638.93 E	16
Apron 6 ASPH PCN 14 F/A/X/T	19	592125.84 N 0175641.98 E	15
Apron 7 ASPH PCN 19 F/B/X/T Narrow part connecting to TWY S PCN 12 F/A/X/T			
Apron Remote North ASPH PCN 101 F/A/X/T			