



Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking	Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar
A	15 m	ASPH PCN 26 F/B/X/T	CL HLDG	EDGE	RGL

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
ASPH PCN 22 F/B/X/T			

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
18	176.69° GEO 172° MAG	600136.57N 0133441.24E GUND 102.1 ft	PCN 25 F/B/X/T	THR 474.3 ft TDZ 474.3 ft	1508	1508	1508	1508	Barrette CL Cat I 900 m LIL/LIH	THR Green	PAPI Left/3.00° (50.0 ft)	1508/60 m White Caution zone 600 m yellow LIL/LIH	Red
36	356.69° GEO 352° MAG	600047.91N 0133446.87E GUND 102 ft	PCN 25 F/B/X/T	THR 469 ft	1508	1508	1508	1508		THR Green	PAPI Left/3.00° (21.5 ft)	1508/60 M White Caution zone 600 m yellow LIL/LIH	Red

